

CAGE LIGHT

PQ-CLW / PQ-CLC
PQ-CNLW / PQ-CLNC

LED VAPORPROOF Cage Lights are designed to replace 100-watt incandescent and 23-watt CFL fixtures with high-quality, longlasting illumination over doorways, scaffolding, construction sites, fire hydrants and emergency call stations.

The lamps are IP66 rated against ingress of dust and pressurized water in harsh environments, and suitable for inverted mounting.

They have an L70 lifetime of 50,000 hours.



LISTINGS



SPECIFICATIONS

Power consumption	14W	Working temperature	-40°C ~ 55°C
Lumens delivered	900lm	IP rating	IP66
Efficacy	80 lm/w	Housing	Aluminum
Color temperature	4000K/5000K	Cover	Frosted PC/Glass
Input voltage	100-277V standard	Certification	FCC, ETL
Lifespan	50000 hrs	Material usage	RoHS compliant, no mercury
Color Rendering Index	>80	Environment	Wet locations
Warranty	5 years	Power factor	>0.9

CAGE LIGHT

PQ-CLW / PQ-CLC / PQ-CLNW / PQ-CLNC

FEATURES

- Efficacy exceeding 80 lm/W allows replacement of 100W incandescent or 23W CFL
- Wide operating temperature of -30°F-104°F
- 70 CRI min
- Universal 110-277V power supply
- Power Factor > 0.9; THD < 25%
- Rated for 50,000-hour L70lifetime at TM-21 standards, 25°C

CONSTRUCTION

- Die-cast housing, durable powder coat finish
- IP66 rated
- Suitable for inverted mounting
- Multiple conduit entries for easy wiring
- One end and two ends connection
- Flat polycarbonate lens allows for lower mounting heights

MOUNTING OPTIONS

Wall Mount



External Driver
PQ-CLW



Internal Driver
PQ-CLW



External Driver
PQ-CLNW



Internal Driver
PQ-CLNW

Ceiling Mount



External Driver
PQ-CLC



Internal Driver
PQ-CLC



External Driver
PQ-CLNC



Internal Driver
PQ-CLNC