

MAGNETIC STRIP

PQ-RKMI

Magnetic Strips are economic LED replacements for 1'x4', 2'x2' and 2'x4' existing recessed troffers in drop-in ceilings. The kits are easily field installed using simple hand tools with minimum modification to the existing housings.

APPLICATION

Replaces traditional fluorescent troffers in lay-in or T-grid ceilings in a variety of commercial applications, including offices, lobbies, hallways and conference rooms in schools, municipalities, libraries, airports, showrooms, corporate campuses, retailers and hospitality environments.



Magnetic



SPECIFICATIONS

Input voltage	100-277V/60Hz	Housing	Plastic
CRI	80	Mounting	Magnetic/Screw
Efficacy(lm/w)	115	Humidity	20%-85% RH, non-condensing
CCT	3000, 3500, 4000, 5000K	Color Consistency	Proprietary binning for uniform color
Beam Angle	140°	Dimmable	available
Power Factor	0.99	Replacements	Retrofit 2'x2', 1'x4', and 2'x4' "troffers" and 4' and 8' linear fluorescent fixtures
Lifetime	50,000Hrs	Environment	Damp-listed
Warranty	5 years limited	Certification	FCC, LM-79, LM-80, UL(driver), ETL, DLC.

MODEL	POWER	LUMENS	LED QTY	LENGTH	FITS FIXTURE
PQ-RKMI22-XXK-020W	20W	2450	2 PCS	550mm	2' x 2' Troffer
PQ-RKMI14-XXK-020W	20W	2500	2 PCS	1100mm	1 x 4'/2x4 Troffer
PQ-RKMI24-XXK-040W	40W	4500	2 PCS	1100mm	2' x 4' Troffer
PQ-RKMI24-XXK-050W	50W	6200	2 PCS	1100mm	4' Fixture
PQ-RKMI28-XXK-050W	50W	6400	4 PCS	1100mm	8' Fixture

XX= Color Temperature : 31K=3000-3500K 41K=4000-4500K 51K=5000-5500K 61K=6000-6500K
 ADD at the end Voltage : 120V, 240V or 347V

LISTINGS

