



L'ÉNERGIE sous un NOUVEAU JOUR
ENERGY in a NEW LIGHT



DOWNLIGHT

◀ PQ-DWLB6

➤ 6 inch downlight

The POWER Q 6inch LED Commercial Downlight are suitable for 100~347 VAC Input with fired-rated junction box, which delivers high lumens of exceptional 80+ CRI, Lifetime > 50000H with 3000K,3500K, 4000K, 5000K ES color temperature options. They can replace most manufacturers incandescent, CFL or H.I.D. fixtures with apertures of 6.1" min.to 6.7" max diameter, Easy replacement and installation can be carried out without removing existing fixture.

PERFORMANCE SUMMARY

Model	PQ-DWLB6-XX	PQ-DWLB6-XX	PQ-DWLB6-XX
Efficacy	100 lm/w	100 lm/w	95 lm/w
Rated Power	18 W	27 W	40 W
Delivered light output	1800 lm	2700 lm	3800 lm
Input Voltage	100-347V AC		
CRI	Ra >80		
CCT Options	3000K, 3500K, 4000K, 5000K		
THD	<20%		
PF	>0.9		
Standard Warranty	5 Years		
Standard Lifetime	Designed minimum 50,000 hours		
Mounting	Recessed, Retrofit		
Recommended Dimmers	DIVA-DVTV(LUTRON), NOVA T NTSTV-DV(LUTRON)		
Signal Current	<2mA		
Driver Efficiency	>87%		
Temperature Rating	Designed to operate in temperature 45°C and below room side and plenum side.		
UL Listed	YES		
Energy Star Listed	YES		
LM79 Report	YES		
Damp Rated	YES		



Dimension

