

IP69 PROOF LAMPS

PQ-WPM

- Ingress protection
- IP69 Proof
- Mechanical strength: IK08-10
- UV resistance
- Ammonia resistance
- Corrosion resistance
- Applications: Car washes, parking lots, meat and other food processing, poultry plants and farms, grocery stores, dairies, low temperature storage



CB

RoHS



SPECIFICATIONS

Diameter: 100 mm

Length	0.6 m	1.2 m	1.5 m
Power	30 W	50 W	80 W

Diameter: 70 mm

Length	0.6 m	1.2 m	1.5 m
Power	20 W	30 W	45 W

Diameter: 48 mm

Length	0.6 m	1.2 m	1.5 m
Power	12 W	24 W	32 W

CRI	≥80
CCT	3000K, 4000K, 5000K
IP Grade	67, 68, 69
IK Grade	09/10
PF	≥0.9
Voltage	100-277V
Safety class	Class I
Lifetime	50000H
Approval	cETL, CB, RoHS, IFS, NSF

PRODUCT SHOWCASE

Φ100 mm LED TUBULAR LUMINAIRE



Φ70 mm LED TUBULAR LUMINAIRE



Φ48 mm LED TUBULAR LUMINAIRE



IP69 PROOF LAMPS

PQ-WPM5

MAIN PARTS



Aluminum housing for heat dissipation



PC + fillings for chemical resistance



Endcap material : PC + fillings



High efficiency LED component
SMD2836 to reach 130lm/W

M16 Cable fitting material:
Copper + plated
Chemical resistance + sealing



LED Waterguard



Chemical gas guard



Farm / Poultry

