FICHE TECHNIQUE

LUMIÈRE ENCASTRÉE ÉLANCÉE

PQ-DWLS

NOUVEAU!

- CCT ajustable 3000-4000-5000K
- Le luminaire encastré de type downlight de 4''' est livré avec un régulateur de tensions externe dans une boîte de jonction. Qualité commerciale avec un design architectural.
- Mince à 1": Convient à un espace de plafond serré.
- Étanche à l'air et certifié IC: Aucun boîtier requis.
- La facilité de l'installation aide à économiser le coût du travail.
- Boîte de jonction incluse: Aucun matériel supplémentaire requis.
- CRI 82: Le rendu des couleurs vraies est une option.
- CCT tunable 3000-4000-5000K, couleur ajustable 3000-4000-5000K
- Certifié ETL: qualité fiable et fonctionnement sûr.
- Convient aux endroits humides.

GARANTIE 5 ANS

Durée de vie 50 000 HRES

IRC 82+ Ra

>0.95 facteur de puissance

ENDROIT HUMIDE

CERTIFICATIONS

SPECIFICATIONS

Input Voltage	120V AC, 50/60 Hz	Color Temperature	2700K-6000K
Efficiency	70 lm/W	Approved Locations	Insulated ceilings
CRI	>82Ra (CRI 90 optional)	Airtight	Yes
Power Factor	0.95	Lamp Life	70% light output at 50000hrs
Warranty	5 years	Certification	ETL, cETL, some models with Energy Star
Beam Angle	110°	Color adjustable	3000K-4000K-5000K

MODEL	POWER (W)	LUMENS	DIMMABLE	DIMENSIONS (mm)	CUTOUT SIZE (mm)	CERTIFICATION
PQ-DWLS-CCTK-10W	10	600-700	CCT + Brightness	122 x 11.5 mm	Φ 108 mm	ETL, cETL
PQ-DWLS-CCTK-12W	12	800-900	CCT + Brightness	173 x 11.5 mm	Φ 158 mm	ETL, cETL
PQ-DWLS-XXK-10W	10	600-700	Triac	122 x 11.5 mm	Φ 108 mm	ETL, cETL, Energy Star
PQ-DWLS-XXK-12W	12	800-900	Triac	173 x 11.5 mm	Φ 158 mm	ETL, cETL, Energy Star
PQ-DWLS-XXK-18W	18	1200-1300	Triac	223 x 11.5 mm	Φ 210 mm	ETL, cETL
PQ-DWLS-XXK-24W	24	1800	–	305 x 11.5 mm	Φ 279 mm	ETL, cETL

XX= Température de couleur 27K = 2700K 31K=3000-3500K 41K=4000-4500K 51K=5000-5500K 61K=6000-6500K
CCTK = 3000-4000-5000K ajustable

9600, Boul St-Laurent, Bureau 300, Montréal, Québec H2N 1R1 • Tél: 514 667-6810 / Télécopieur : 514 667-5722 • info@power-q.ca