

# IMPACT RESISTANT LED LIGHTING FOR PRISON

## PQ-LIDL

- Optically engineered system
- Excellent thermal control
- High efficiency LED tube
- Fast and easy to install, saving on labor
- Energy saving up to 70%
- 3-layer lens to protect from impacts
- Tamper-proof screws



### SPECIFICATIONS

Input Voltage	120-347V	Rated	IK10, IP65
CRI	>80	Housing	Steel with white powder coating
Color temperature	5000K-4000K-3000K	Diffuser	6+3+1 mm 3 layer PC
Angle	120°	Reflector	Aluminum
Lifespan	50,000 hrs		



MODELS	POWER (WATTS)	SIZE (INCHES)	LUMENS PER WATT
PQ-LIDL	20W	27.5 × 12.2 × 3.15 IN	130 lm/w
PQ-LIDL	40W	27.5 × 12.2 × 3.15 IN	
PQ-LIDL	30W	51.2 × 12.2 × 3.15 IN	
PQ-LIDL	60W	51.2 × 12.2 × 3.15 IN	
PQ-LIDL	20W	27.5 × 12.2 × 3.15 IN	105 lm/w
PQ-LIDL	40W	51.2 × 12.2 × 3.15 IN	
PQ-LIDL	50W	51.2 × 12.2 × 3.15 IN	
PQ-LIDL	60W	51.2 × 12.2 × 3.15 IN	

LIDL is with LED Tubes 10W/15W  
 LIDL is LED 2845  
 ADD 051K=5000K, 041K=4000K, 031K=3000K  
 ADD 002P=2FT, 004P=4FT  
 Dimmable 0-10V only on LIDL

**Example P/N : PQ-LIDL-051K-40W-UNIV-D-004P**

# IMPACT RESISTANT LED LIGHTING

PQ-LIDL

## APPLICATION

---

**PQ-LIDL lighting are engineered to withstand clever entry and concealment attempts. These luminaires are crafted to endure the most extreme abuse across all security levels.**

