

UFO HIGH BAY

PQ-HBG

Available in three sizes, the HBG UFO high bay with the ability to switch lumens and adjust CCT in one fixture, making it versatile enough to handle countless applications.

- **Power Selectable:** 150TW, 200TW, 240TW & 320TW
- **CCT:** Selectable between 4000K & 5000K
- HBG provides 150lm/w (standard) and 170lm/w light efficacy options, which will assure the brightness meets the application and provides the amount of light you want and need for your area during install.
- Standard with 0-10V sensor port, for quick plug and play install sensor. The fixture is DLC LLLC listed also compatible with NLC system. Emergency battery backup is available.
- IP65 rated products, suitable for commercial and industrial: warehouses and storage, industrial facilities, retail centers, manufacturing, sports facilities and gymnasiums.



4000K 5000K



0-10V

4000K
5000K

UFO HIGH BAY

MODEL	Color Temperature (CCT)	Power Tunable (TW)	Luminous Flux (Lm)	Dimensions (mm) (W x H)	Input Voltage (V)
PQ-HBG	CCTK = 4000K/5000K	150TW = 150/100/80 200TW = 200/150/100 240TW = 240/200/150 320TW = 320/240/200	25,500lm 34,000lm 40,800lm 54,400lm	275 x 196 275 x 196 305 x 200 350 x 220	UNIV = 120-347 VAC

CERTIFICATIONS



UFO HIGH BAY

PQ-HBG


SPECIFICATIONS				
Models	150TW	200TW	240TW	320TW
Power Tunable (TW)	150/100/80	200/150/100	240/200/150	320/240/200
Input Voltage (V)	120-347VAC			
Frequency (Hz)	50-60			
Dimmable	0-10V			
Color Temperature	4000K, 5000K			
Beam Angle	60°, 90°, 120°			
Lumen per Watt	150L/w standard, 170L/w optional			
CRI	>80			
Cables	5ft (59") power cord 1ft (12") dimming cord			
Housing	Die-casing aluminum			
Color Finish	Black or White			
Operating temperature	-40°F (-40°C) to 122°F (50°C)			
Mounting	Standard with G hook & Safety rope 0.3m Optional: O hook, U bracket, and 3/4" NPS Threaded Pendant mount adapter are available.			
Sensor	Microwave or PIR (Optional)			
Certifications	cULus, DLC			
Warranty	5 years			

UFO HIGH BAY


PQ-HBG

DIMENSIONS (IN MM & INCHES)


SMALL SIZE - 150TW & 200TW



MEDIUM SIZE - 240TW



LARGE SIZE - 320TW



UFO HIGH BAY

PQ-HBG



SMALL SIZE - 150TW & 200TW



MEDIUM SIZE - 240TW



LARGE SIZE - 320TW

UFO HIGH BAY

PQ-HBG

ORDERING GUIDE

MODEL	Color Temperature (CCT)	Power Tunable (TW)	Input Voltage (V)	Beam Angle	Housing Color	Options
PQ-HBG	CCTK = 4000K/5000K	150TW = 150/100/80 200TW = 200/150/100 240TW = 240/200/150 320TW = 320/240/200	UNIV = 120-347VAC	060D = 60° 090D = 90° 120D = 120°	NR = Black BL = White	SM = Microwave Sensor SPIR = PIR Sensor

Catalog Number as an Example: PQ-HBG-CCTK-240TW-UNIV-120D-NR-SPIR

If you have customized technology needs or specific services requirements, we strongly recommend contacting Power-Q's experts


EMAIL: info@power-q.ca

PHONE: 514 667-6810


UFO HIGH BAY

PQ-HBG


PHOTOMETRY



120°



90°



60°

POWER SELECTION



Power Setting

Adjust power between

Small:

150/100/80W, 150W default setting.

200/150/100W, 200W default setting.

Medium:

240/200/150W, 240W default setting.

Large:

320/240/200W, 320W default setting.

CCT Setting

Adjust CCT between

4000/5000K, 5000K default setting.

UFO HIGH BAY

PQ-HBG

OPTIONAL ACCESSORIES

Sensor : Factory-Installable OR Field-Installable (field-installable purchased separately)

	SM = Microwave Sensor		SPIR = PIR Sensor
---	-----------------------	---	-------------------

Field-Installable / Field-Use ONLY (purchased separately)

	Remote Control
---	----------------

Mounts and Brackets : Field-Installable (field-installable purchased separately)

	Small Size U Bracket		0.3m Safety Rope (Included)
	External Threads M10 to External Threads 3/4"NPS Adapter Wiring for 150TW to 240TW		External Threads M12 to External Threads 3/4"NPS Adapter Wiring for 320TW only
	0.5m Stainless Steel Hang Chains with 2pcs Carabiner		

Reflector : Field-Installable (field-installable purchased separately)

	Smaller Size (12.20x5.04") Polycarbonate Refractor		Smaller Size (12.20x6.14") Polycarbonate Refractor with Drop Lens
	Small Size (16.22x5.91") Polycarbonate Refractor		Small Size (16.22x7.36") Polycarbonate Refractor with Drop Lens
	Large Size (16.22x5.71") Polycarbonate Refractor		Large Size (16.22x7.17") Polycarbonate Refractor with Drop Lens